Product info

Hi-Temp Wax Dry Spray Transparent

Art.: 02.2119.6100
Aerosol can 500 ml



Hi-Temp Wax Dry is a highly durable, tack-free wax coating made from microcrystalline waxes. It provides excellent rust protection in factory original quality for sheet metal parts, vehicle undersides, suspension components, and (machine) parts. The product has excellent penetration and water-repellent properties, enabling it to reach even the smallest crevices and protect surfaces reliably and for the long term. Thanks to the addition of a UV indicator, the presence of Hi-Temp Wax Dry can always be detected.

Hi-Temp Wax Dry has an extremely high temperature resistance due to its special chemical composition. The product remains absolutely stable up to a temperature of 170°C. Due to its very high temperature resistance Hi-Temp Wax Dry is extremely well suited for use in the engine compartment of the vehicle and in engine rooms - the product will not run off. Hi-Temp Wax Dry is used to protect metal and sheet metal against corrosion during construction or repair of vehicles. After drying, Hi-Temp Wax Dry is completely tack-free and therefore also perfectly suitable for rust protection during transport and interim storage of metal parts.

Hi-Temp Wax Dry is also ideal for protecting power points and battery poles subject to the effects of weather, moisture, dirt and salt. Hi-Temp Wax Dry ensures that these parts are highly water-repellent, minimizing disturbances due to penetrating moisture or corrosion.

Hi-Temp Wax Dry is available in different types of packaging: besides the aerosol can and the 1 litre screw-top can, the product is also deliverable as a 60 litre and 200 litre barrel.
Spraying of the 1 l screw-top can is done using a traditional gun such as the Innotec Pressure Gun Basic (4-6 bar) or the Pressure Pot Gun specially developed for this purpose (2-4 bar, possibly in combination with the special Cavity Tube Set for hollow spaces), but can also be done with the Multi Sprayer 1,3 l.
The 60 l and 200 l barrels are sprayed with a traditional gun or with the Multi Sprayer 1,3 l.
The aerosol can is extremely user-friendly and easy to apply. The product is initially liquid when applied, allowing it to spread evenly over the surface. Once the propellant has evaporated, a smooth, solid, and protective coating remains. The extra nozzle and tube supplied with the product make it very easy to apply in places which are difficult to access. For optimal treatment of cavities use the Hi-Temp Wax Spray Tube.

- Good flow qualities during application.
- No dripping after application.
- Perfect protection against corrosion.
- Aromatic/silicone free, almost odourless.
- Temperature resistant up to +170°C.
- Insensitive to brake fluid and salt.
- No disassembly of plastic & rubber parts required.
- Contains UV indicator.
- OEM approved.

www.innotec.eu/1927

A member of group
PCS Innotec International N.V.