Technical info

Hi-Temp Wax Dry Spray Transparent

Art.: 02.2119.6100
Aerosol can 500 ml

Hi-Temp Wax Dry is a highly durable, tack-free wax coating made from microcrystalline waxes. It provides excellent rust protection in factory original quality for sheet metal parts, vehicle undersides, suspension components, and (machine) parts. The product has excellent penetration and water-repellent properties, enabling it to reach even the smallest crevices and protect surfaces reliably and for the long term. Thanks to the addition of a UV indicator, the presence of Hi-Temp Wax Dry can always be detected.



Base:	Microcrystalline waxes and sulfonates
Density:	± 774 kg/m³
Consistency:	Liquid (ready-to-use in aerosol)
Solvents:	Mixture of aromatic and aliphatic solvents
Flash point:	< 0°C
Temperature resistance:	-40°C to +170°C
UV resistance:	Prolonged exposure may result in ageing or discolouration.
Water resistance:	Excellent
Solvent resistance:	Good
Tests:	Excellent resistance to corrosion according to ISO 9227 (more than 500 hours)
Application conditions:	+15°C to +35°C
Type of surface:	Ferrous and non-ferrous metals
Surface preparation:	The surface must be clean, dry and free of grease. Clean surfaces with Innotec Multisol or Innotec Seal and Bond Remover.
Application method:	Shake can well before use. Spraying distance 20-25 cm. Apply a dense and evenly sprayed layer. When applying to cavities, use the special Hi-Temp Wax Spray Tube. After use, invert can and spray until clear to clean the nozzle.
Tack free:	After ± 3 days (100µ layer thickness (wet) / at 20°C / 65% relative humidity and with adequate ventilation)
Dust dry:	After ± 24 hours (100µ layer thickness (wet) / at 20°C / 65% relative humidity and with adequate ventilation)
Recommended layer thickness:	± 220µ (wet), ± 50µ (dry)
Paintability:	Not paintable
Cleaning of materials used:	With Innotec Multisol

www.innotec.eu/1927

PCS®
A member of group
PCS Innotec International N.V.

Cleaning of hands:	With Innotec Power Scrubs or with Innotec Safe Hand Clean Plus and water
Shelf life:	2 years in original, unopened packaging
Storage conditions:	Store cool and dry
Type of batchcode:	F
EAN Code:	5400563036716

This technical info sheet replaces all previous versions.

All information is supplied without obligation and based on our knowledge and experience with the product under normal conditions. In practice, the information supplied can in no way replace the tests that need to be performed before first use of the product. only prior testing of the product can prove whether the product is indeed suitable for the intended application (or not). Thus, we cannot accept any responsibility in case our products are not used in compliance with the advices given.

If the product should not meet the quality requirements, we will only reimburse up to a maximum of the purchase price of the product. We accept no responsibility whatsoever and shall under no circumstances be liable for damage or consequential loss arising from the use of the product.

For information concerning safe use and storage, please refer to the safety data sheet of the product concerned.

www.innotec.eu/1927

A member of group
PCS Innotec International N.V.