Technical info

High Trib Oil 500 ml

Art.: 03.1175.9999
Aerosol can 500 ml

High Trib Oil is an extremely high-quality and versatile lubricating oil with TRIBITEC technology, which guarantees excellent lubrication even under high pressure and temperature loads.



Base:	Mixture of semi-synthetic oils, enriched with Extreme Pressure (EP) and Anti-Wear (AW) additives
Density:	755 kg/m³
Consistency:	Thick liquid (ready-to-use in aerosol)
Kinematic viscosity:	<= 20,5 mm²/s (40°C)
Flash point:	< 0°C
Pressure resistance:	Very good thanks to synthetic oils and Extreme Pressure (EP) and Anti-Wear (AW) additives
Temperature resistance:	-30°C to +260°C
Water resistance:	Good
Acid resistance:	Resistant to diluted acids
Corrosion resistance:	Very good
Penetration ability:	Very good due to the addition of surfactants
Percentage of greasing agent:	± 60%
Tests:	Wear Scar (method IP239, 40 kg, 60 min, 1450-1500 rpm, room temperature): 0,62 mm
Application conditions:	+5°C to +40°C
Type of surface:	All kind of metals and most plastics
Surface preparation:	The surface must be clean, dry, free of grease and non-corroded. Clean surfaces with Innotec Multisol, Innotec Ultra Clean or Innotec Power Clean.
Application method:	Shake well before use. Spray directly on the part to be lubricated and leave a short time to evaporate.
Cleaning of materials used:	With Innotec Multisol or Innotec Power Clean
Cleaning of hands:	With Innotec Power Scrubs or with Innotec Safe Hand Clean Plus and water
Shelf life:	1 year in original, unopened packaging
Storage conditions:	Store cool and dry
Type of batchcode:	F

www.innotec.eu/2382

PCS®
A member of group
PCS Innotec International N.V.

Other details:	Never spray on excessively hot surfaces (> 90°C), as toxic gases may be released due to accelerated evaporation.
EAN Code:	5400563039038

This technical info sheet replaces all previous versions.

All information is supplied without obligation and based on our knowledge and experience with the product under normal conditions. In practice, the information supplied can in no way replace the tests that need to be performed before first use of the product. only prior testing of the product can prove whether the product is indeed suitable for the intended application (or not). Thus, we cannot accept any responsibility in case our products are not used in compliance with the advices given.

If the product should not meet the quality requirements, we will only reimburse up to a maximum of the purchase price of the product. We accept no responsibility whatsoever and shall under no circumstances be liable for damage or consequential loss arising from the use of the product.

For information concerning safe use and storage, please refer to the safety data sheet of the product concerned.

www.innotec.eu/2382

A member of group
PCS Innotec International N.V.